



WOOD SOLUTIONS

**ALL WOOD
JOBS COVERED**



TOUPRET[®]
FILLERS FOR PROFESSIONALS



Toupret's wood range is a total solution for bringing wood back to life. No matter the job, you can rely on Toupret's system of products to carry out your restoration project, from hardening rotten wood to repairing, reshaping, filling and fine finishing, as well as glazing wooden window frames.

Wood comes in many species of hardwoods and softwoods, used for a variety of different purposes, indoors and out, in both construction and decoration. Toupret's range has therefore been designed to allow you to restore all wood, regardless of where it is and how it's used, from balustrades to window frames, front doors to skirting boards.



NEW!

Create the ultimate finish to doors, windows and all wood surfaces with **FINE FINISH WOOD FILLER.**

- Ready to paint, stain or varnish in 1 hour
- Compatible with all paints and coatings

ANY CHANCE OF PRODUCING IT IN WHITE???

TRADE PROFESSIONAL
Instagram (2024)
Refers to Wood Repair Filler

YOU ASKED WE DELIVERED

INTRODUCING...



**COLOUR:
WHITE**

AVAILABLE IN
Colours: Natural Wood
and White
Sizes: 1kg and 2kg



**COLOUR:
OFF-WHITE**

AVAILABLE IN
Colours: Natural Wood
and Off-White
Sizes: 330g and 1.25kg

REPAIR AND RESTORE

WOOD

NEED HELP?

Find the right product in a few easy steps with Toupret's Product Selector

PREPARE

WOOD HARDENER

Improves adhesion of fillers & coatings on interiors & exteriors

- Toughens rotten wood
- Adheres to damp wood
- Deep penetrating
- Water based

COLOUR:
WHITE



1L

REPAIR

WOOD FILLER

Ready to use on interiors & exteriors

- Easy to apply and sand
- Compatible with all paints & coatings
- Can be drilled & screwed
- Low odour

COLOUR:
NATURAL WOOD

COLOUR:
OFF-WHITE



330G, 1.25KG

WOOD REPAIR FILLER

Easy to shape & quick drying on interiors & exteriors

- Working time: 30 minutes
- Easy to sand
- Compatible with all paints & coatings
- Can be drilled & screwed
- Low odour

COLOUR:
NATURAL WOOD

COLOUR:
WHITE



1KG, 2KG

FINISH

FINE FINISH WOOD FILLER

Extra fine smoothing on interiors & exteriors

- Covers small defects
- Flexible
- Quick Drying
- Compatible with all paints & coatings

COLOUR:
WHITE



400G

GLAZE

GLAZING PUTTY

Flexible - will not crack on interiors & exteriors

- Long-lasting
- Compatible with all paints & coatings
- Doesn't stick to your hands
- Will not smear on glazing

COLOUR:
WHITE



1KG

Ask yourself:

1 LOCATION

Is the job inside or out?

2 SURFACE CONDITION

Is the surface hard, cohesive, clean, sound and dry?

3 SURFACE TYPE

What are you working on? Primed wood or bare?

4 TASK

Are you treating? Filling? Repairing? Smoothing?

CHECK IT OUT!

Head to **Professional Services** on our app and website



FILL

HOW TO REPAIR A GAP, CRACK OR HOLE



1. PREPARE

by removing any loose pieces or particles and dusting off. If filling fine cracks and gaps, open them up by scraping them out with a shave hook or scraper.



2. FILL

by applying plenty of filler to the cavity using a filling knife. Fill gradually and apply from several directions to make sure you don't leave any air pockets.



3. SMOOTH

by passing over in different directions, starting from the centre of the filled area each time. Sand when the filler is dry and ready to paint.

REPAIR

HOW TO REPAIR A BROKEN EDGE



1. REMOVE

loose parts and dust away debris.



2. RECONSTRUCT

the rough shape using a filling knife.



3. WAIT

as the filler begins to harden and sculpt it with your blade.



4. SAND

when the filler is dry and ready to paint.

FINE FINISH

HOW TO HIDE SCRATCHES, MARKS OR IMPROVE THE OVERALL FINISH



1. PREPARE

the surface by dusting off any loose particles and prime.



2. APPLY

once the primer is dry, up to 1mm thick with the use of a filling blade or knife.



3. REMOVE

any excess with your blade or knife held at a tight angle.



4. SAND

when the filler is dry and ready to paint.

HARDEN

HOW TO TOUGHEN ROTTEN WOOD



1. PREPARE

by removing any loose pieces or particles and dusting off.



2. APPLY

using the accompanying brush attached to the inside of the lid.

GLAZE

HOW TO GLAZE SINGLE PANE WOODEN WINDOWS



1. PREPARE

by removing any previous paint and putty with the use of a scraper.



2. APPLY

the putty by rolling a small ball and pushing sections into and along the rebate with your thumb or putty knife.



3. SMOOTH

over with a putty knife in one steady, smooth movement, then roll your finger over to remove any excess.

GREAT GEAR THIS

TRADE PROFESSIONAL
Instagram (2024)
Refers to Wood Repair Filler

BEHIND A GREAT SKILL SITS A FANTASTIC PRODUCT

TRADE PROFESSIONAL
Instagram (2024)
Refers to Wood Repair Filler

AT YOUR SERVICE



TRAINING & PROJECT SUPPORT

- For information on future demonstration events or for specific training or advice, contact our office and we will direct you to one of our technical field team.



TECHNICAL ASSISTANCE

- For urgent technical or commercial questions, contact our expert customer support: projects specifications, product features, standards, arranging visits or meetings at your local merchant: toupretuk@toupret.com or 0208 916 2134. Monday to Friday 9am to 5pm.



ONLINE SUPPORT 24/7

- Expert advice, detailed product information, selection advice, application videos: toupret.co.uk

TOUPRET (UK) LIMITED

Capital Business Centre
Unit 58, 22 Carlton Road
South Croydon CR2 0BS
Tel: +44 (0)208 916 2134
www.toupret.co.uk



Recyclable paper



DOWNLOAD THE TOUPRET APP

All the product information, news and advice you need, straight from your phone.



TOUPRET[®]
FILLERS FOR PROFESSIONALS

FOLLOW US

toupret.co.uk     