

AIRLESS JOINTING PLASTER

FOR JOINTING & SKIMMING

- ◆ FINE FINISH
- ◆ SMOOTH GLIDE
- ◆ EASY TO SAND
- ◆ UKCA & CE CERTIFIED FOR JOINTING



PURPOSE

Ready to use airless spray plaster for interior jointing and skimming of plasterboard.

SUBSTRATES

Airless Jointing Plaster can be applied to new or renovated substrates, painted or unpainted:

- Gypsum, plasterboard/drywall, old painted substrates, cement, concrete, cellular concrete.
- There is no need to prime or seal the surface before application.

OVERCOATING

Airless Jointing Plaster can be coated with all types of fillers, paint or wall coverings.

PHYSICAL AND TECHNICAL FEATURES

- Airless Jointing Plaster: ready to use filler for interior use, made of mineral components and synthetic resin.
- Characterisation (NFT 36-005): Family III - Class 2.
- Codification (EN 16566): G₃S₁V₀W₀A₀C₀R₀
- Mixing rate: ready to use.
- Application thickness: up to 5mm.
- Coverage: 1.7kg/m²/mm.
- Setting time: second coat as soon as the filler is hard and dry to the touch.
- Overcoating: can be painted in 24 to 48 hours average time (after completely dry).
- Colour: white.
- Adhesion: filler/substrate (EN 16566): > 0.5 Mpa.

USE AND STORAGE CONDITIONS

- Application tools: any type of airless spray machine with minimum flow rate of 5L/min. For optimum use, we recommend the following nozzles: 3.31 to 6.35.
- Tools cleaning: with water.
- Preservation: Toupret products are designed for high performance and are guaranteed for 12 months from purchase when used as intended. If the product is found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase. Product should be kept in its original sealed packaging and stored away from sunlight and frost.

PACKAGING

- 25kg bag.

RECOMMENDATIONS AND CARE FOR USE

- The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.
- Do not apply at a temperature below 8°C or above 35°C nor at a relative humidity over 70%.
- Do not apply on overheated surfaces.
- Do not apply on damp substrates.
- Do not apply on polystyrene, wallpaper, or exterior substrates.

SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS TO BE REFERRED TO

- BS EN 16566: Fillers for internal and/or external works.
- NF EN 16566: Fillers for internal and/or external works.
- NFT 36-005: Characterisation of paint products.
- DTU 59.1 (NFP 74-201): Building paint works.
- DTU 25.41 (NFP 72-203-1) Building works - Gypsum plasterboard works - Gypsum wallboards.
- BS EN 13963: Jointing materials for gypsum boards.
- NF EN 13963: Jointing materials for gypsum boards.

HEALTH AND SAFETY

It is recommended to wear a dust mask when sanding. It is recommended to wear protective gloves and eye protection during product application. Dispose of unused product and packaging responsibly at your local waste collection centre.

Contains biocidal products (Preservatives for products during storage): Contains 1,2-benzisothiazolin-3-one ; 2-methylisothiazolin-3(2H)-one ; C(M)IT / MIT (3 : 1). May produce an allergic reaction. Safety data sheet available on request.

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from Toupret's experience and knowledge of the products.

The product should be used as per the trade practices rules book and in reference to our recommendations.

The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates.



* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).