

# FINE AND ADHESIVE SCRIMS

## FINE AND ADHESIVE SCRIMS TAPES FOR CRACK TREATMENT

- ◆ **STRONG ADHESION**
- ◆ **EASY AND QUICK TO INSTALL**
- ◆ **EASY TO OVERCOAT**
- ◆ **90m x 48mm**



### PURPOSE

Scrim tapes for the treatment and reinforcement of inert and moving cracks and joints - Interior and exterior use.

### SUBSTRATES

Can be applied to any tapered or butted plasterboard.

### OVERCOATING

Fine and adhesive Scrim can be covered with any type of filler, paint or wall covering.

### PHYSICAL AND TECHNICAL FEATURES

Fine scrim is made from knitted polyamide.  
Adhesive scrim is made from knitted polyester.

- Dimensions:  
Fine scrim: 5 m x 5 cm or 20 m x 5 cm.  
Adhesive scrim: 50 m X 5 cm.
- Weight per square meter:  
Fine scrim: 29 grams.  
Adhesive scrim: 52 grams.
- Elongation:  
Fine scrim: 70 % in wide and 10% in length.  
Adhesive scrim: 50 %.
- Limit of breaking strength of the scrims:  
Fine scrim: for a 5 cm wide tape, the resistance limit is 14 kg in length - 17 kg in width.
- Adhesive scrim: 318 daN per metre length

### USE AND STORAGE CONDITIONS

- Application tools: filling knife.
- Preservation: product guaranteed under storage conditions in a dry environment and at constant temperature.

### RECOMMENDATIONS AND CARE FOR USE

- 1- Ensure that the surface is clean and dust-free. Then apply the self-adhesive side directly onto the surface.
- 2- Cover the tape completely with a thin coat of joint filler and allow it to dry.
- 3- After the first coat is dry, lightly sand the surface with the appropriate grade sandpaper for whichever jointing compound is used.
- 4- To finish, cover with a further coat of joint filler.

### SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices.  
Substrates must be hard, cohesive, clean, sound and dry.

### HEALTH AND SAFETY

- The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from Toupret's experience and knowledge of the products.  
The product should be used as per the trade practices rules book and in reference to our recommendations.

#### Manufacturer :

TOUPRET SA  
24 rue du 14 juillet  
91813 CORBEIL ESSONNES CEDEX France  
RCS Evry B 964 201 859 – Mise à jour Avril 2025



\* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).

**TOUPRET**  
FILLERS FOR PROFESSIONALS