

ANTI-DAMP TREATMENT HUMISTOP

MOISTURE BARRIER

- ◆ **BLOCKS LOCALISED PROBLEM MOISTURE**
- ◆ **COVERS MICRO-CRACKS**
- ◆ **APPLY WITH BRUSH OR ROLLER**



PURPOSE

Ready to use anti-damp treatment that acts as a moisture barrier to block problem moisture and cover micro cracks. Apply with a brush or roller.

SUBSTRATES

Anti-Damp Treatment can be applied to damp but not dripping substrates :
- Old painted substrates, cement, bricks and stone.

OVERCOATING

Anti-Damp Treatment can be overcoated by any type of current paint or coating.

PHYSICAL AND TECHNICAL FEATURES

Anti-Damp Treatment: is a water based filler, for exterior and interior use, made of mineral and synthetic binder.

- Characterization (NFT 36-005): Family I class 7b2.
- Directive 2004/42/CE: category A/a (VOCs 2010): maximum 15 g/L.
- Mixing rate: ready to use.
- Coverage: 3m² per kg for 2 coats.
- Setting time: second coat 8 hours average time (application: in two cross coats).
- Overcoating: can be painted in 24 hours average time (after complete drying).
- Colour: white.

USE AND STORAGE CONDITIONS

- Application tools: brush or roller.
- Tool cleaning: after use, clean tools with water.
- Preservation: guaranteed for 12 months from purchase when used as intended, kept in its original sealed packaging and stored away from sunlight and frost. If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

PACKAGING

Tin: 1kg and 5kg.

RECOMMENDATIONS AND CARE FOR USE

- Do not apply on overheated surfaces.
- Do not apply at a temperature below 5°C or above 35°C nor at a relative humidity over 80%.
- Do not apply on damp substrates.

SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS TO BE REFERRED TO

- NFT 36-005: Characterization of paint products.

HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Anti-Damp Treatment.

Dispose of unused product and packaging responsibly at your local waste collection centre.

Contains biocidal products (Preservatives for products during storage) : Contains : IPBC ; 1,2-benzisothiazolin-3-one ; C(M)IT / MIT (3: 1). May produce an allergic reaction. Safety data sheet available at www.toupret.co.uk

VOC emissions <0,5%.

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).

Manufacturer :

TOUPRET SA
24 rue du 14 juillet
91813 CORBEIL ESSONNES CEDEX France
RCS Evry B 964 201 859 – Mise à jour Avril 2025

TOUPRET
FILLERS FOR PROFESSIONALS