

# MUR EX® ROCK SOLID REPAIR FILLER

## EXTREME DURABILITY & ADHESION ON ANY SUBSTRATE

- ◆ RICH IN RESIN
- ◆ FILLS & REPAIRS ALL SUBSTRATES
- ◆ SHAPEABLE - REPAIR WITHOUT FORMWORK
- ◆ NO NEED TO SEAL THE SUBSTRATE \*



### PURPOSE

MUR EX®, sets to a rock hard finish with exceptional adhesion.  
Can be used on all substrates.

### SUBSTRATES

MUR EX® can be applied to new or renovated, painted or unpainted substrates:  
- Old painted surfaces, cement, concrete  
- Breeze blocks, bricks, stones, glass and glazed tiles.

### OVERCOATING

MUR EX® can be overcoated with any type of filler, paint or wall coating.  
Do not coat directly with polyurethane paints nor epoxy solvent based paints.

### PHYSICAL AND TECHNICAL FEATURES

MUR EX® : exterior filler in powder form, made of cement, selected quarry materials and resin.

- Characterization (NFT 36-005): Family IV class 4c.
- Codification (EN 16-566): G<sub>3</sub>S<sub>2</sub>V<sub>0</sub>W<sub>0</sub>A<sub>0</sub>C<sub>0</sub>R<sub>0</sub>.
- Mixing rate: add 450ml water per 1kg powder (45%).
- Application thickness: no depth limit.
- Capacity: 1kg fills 1L when mixed.
- Working time: 30 minutes.
- Setting time: second coat as soon as the filler is hard and dry to the touch.
- Overcoating: can be painted in 24 hours average time (after complete drying).
- Colour: white.
- Adhesion: filler/substrate (EN 16-566): > 0.8 Mpa.

### USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or blade.
- Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
- Preservation: product guaranteed 6 months. Stored away from humidity. If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

### PACKAGING

Box: 2kg.  
Bag: 5 kg and 15 kg.

### RECOMMENDATIONS AND CARE FOR USE

- Do not apply under a temperature below 5°C and above 35°C nor under a hygrometry rate over 80%.

### SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices.  
\*Substrates must be hard, cohesive, clean, sound and dry.

### NORMATIVE DOCUMENTS TO BE REFERRED TO

- BS EN 16566:2014 (Paints and varnishes. Fillers for internal and/or external works).

### HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying MUR EX®.  
Always wear a dust mask when sanding.  
Dispose of unused product and packaging responsibly at your local waste collection centre.  
Safety data sheet available at [www.toupret.co.uk](http://www.toupret.co.uk)

### UFI: YY4W-UK24-HRHF-M9FX

Contains cement – please read the care for use guidelines on the packaging or on the MSDS before handling.

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products.  
The product should be used as per the trade practices rules book and in reference to our recommendations.  
The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates.  
The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.

#### Manufacturer :

TOUPRET SA  
24 rue du 14 juillet  
91813 CORBEIL ESSONNES CEDEX France  
RCS Evry B 964 201 859 – Mise à jour Avril 2025

**TOUPRET®**  
FILLERS FOR PROFESSIONALS