

# PATCH & REPAIR FILLER

QUICK DRY

## FOR GAPS, CRACKS, SCRATCHES & HOLES

- ◆ ONE COAT
- ◆ EASY TO SAND
- ◆ NO SHRINKAGE, NO DEPTH LIMIT
- ◆ NO NEED TO SPOT PRIME



### PURPOSE

Quick drying interior repair filler for gaps, cracks, scratches and holes on plasterboard and all internal substrates.

### SUBSTRATES

Patch & Repair Filler Quick Dry can be applied to:

- Gypsum, plaster board, old painted surfaces, cement, concrete, cellular concrete and primed wood.

### OVERCOATING

Patch & Repair Filler Quick Dry can be coated with any type of filler, paint or wall coating.

### Physical and technical FEATURES

- Patch & Repair Filler Quick Dry: filler in powder form, made of selected quarry material and resin.
- Characterization (NFT 36-005): Family III - Class 3.
- Codification (EN 16-566):  $G_3S_2V_0W_0A_0C_0R_0$ .
- Mixing rate: add 450ml water per 1kg powder (45%).
- Application thickness: no depth limit.
- Coverage: 1kg fills 1L when mixed.
- Working time: 40 minutes.
- Setting time: second coat 45 mins.
- Overcoating: can be painted in 3 hours average time (after complete drying).
- Color: white.
- Adhesion: filler/substrate (EN 16566): > 0.5 Mpa.

### USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or blade.
- Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
- Preservation: guaranteed for 12 months from purchase when used as intended, kept in its original sealed packaging and stored away from humidity. If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

### PACKAGING

- Boxes: 1kg and 2kg
- Bag: 5kg.

### RECOMMENDATIONS and care for use

The times mentioned are indicative and depend on the substrate, coat thickness, and the ambient conditions. Do not apply at a temperature below 8°C or above 35°C nor at a relative humidity over 70%.

### SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

### NORMATIVE DOCUMENTS to be referred to

- BS EN 16566:2014 (Paints and varnishes. Fillers for internal and/or external works).
- EN 16-566: Coating Fillers for interior and/or exterior works.
- NFT 36-005: Characterization of paint products.
- DTU 59.1 (NFP 74-201): Building paint works.
- DTU 59.4 (NFP 74-204) : Wall papers and wall coatings works.

### HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Patch & Repair Filler Quick Dry.

Always wear a dust mask when sanding.

Dispose of unused product and packaging responsibly at your local waste collection centre.

Safety data sheet available at [www.toupret.co.uk](http://www.toupret.co.uk).

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



\* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).