

PATCH & REPAIR FILLER

READY TO USE

FOR GAPS, CRACKS, SCRATCHES & HOLES

- ◆ EASY TO SAND
- ◆ EXCELLENT ADHESION
- ◆ NO NEED TO SPOT PRIME
- ◆ DOES NOT FLASH OR GRIN



PURPOSE

Ready mixed interior repair filler for gaps, cracks, scratches and holes on plasterboard and all internal substrates.

SUBSTRATES

Patch & Repair Filler Ready To Use can be applied to:
- Gypsum, plaster board, old painted surfaces, cement, concrete, cellular concrete and primed wood.

OVERCOATING

Patch & Repair Filler Ready To Use can be coated with any type of filler, paint or wall coating.

Physical and technical FEATURES

- Patch & Repair Filler Ready To Use : filler in ready mixed form for interior use, made of mineral extracts and selected resin.
- Characterization (NFT 36-005): Family III class 2.
- Codification (NFT 30-608): $G_3E_5S_2V_0W_0A_0C_0$.
- Mixing rate: ready to use.
- Application thickness: up to 1cm.
- Coverage: 1kg fills 0.65L.
- Working time: unlimited.
- Setting time: second coat as soon as the filler is hard and dry to the touch.
- Overcoating: can be painted in 12 to 24 hours average time (after complete drying).
- Color: white.
- Adhesion: filler/substrate (NFT 30-608): > 0,5 MPa.

USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or blade.
- Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
- Preservation: product guaranteed 12 months. Stored away from sunlight and frost. If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

PACKAGING

- Tub: 1.5kg.

RECOMMENDATIONS and care for use

The times mentioned are indicative and depend on the substrate, coat thickness, and the ambient conditions. Do not apply at a temperature below 8°C or above 35°C nor at a relative humidity over 70%.

SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS to be referred to

- BS EN 16566:2014 (Paints and varnishes. Fillers for internal and/or external works).
- NFT 30-608: Coating fillers for interior works and/or exterior.
- NFT 36-005: Characterization of paint products.
- French DTU 59.1 (NFP 74-201): Building paint works.
- French DTU 59.4 (NFP 74-204): Application procedures of wall.

HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Patch & Repair Filler Ready To Use. Always wear a dust mask when sanding. Dispose of unused product and packaging responsibly at your local waste collection centre.

Preservatives: Contains 1,2-benzisothiazolin-3-one; C(M)IT / MIT (3:1); MBIT. May produce an allergic reaction.

Safety data sheet available at www.toupret.co.uk.

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).