

QUICK DRY FILLER

**FILL, REPAIR WITHOUT FORMWORK,
SEALS IN RECORD TIME.**

- ◆ **ULTRA STRONG AND DURABLE**
- ◆ **MULTI-PURPOSE**
- ◆ **MULTI-SUBSTRATES**



PURPOSE

Interior/Exterior powder filler for repairs, gaps, cracks on walls and ceilings.

SUBSTRATES

Quick Dry Filler can be applied to either new or renovated substrates, unpainted or painted:

- Gypsum plaster, plasterboards/drywall lining
- Old painted surfaces, cement, concrete, cellular concrete, breeze blocks, bricks, stone.

OVERCOATING

Quick Dry Filler can be overcoated with any type of filler, paint or wall coating.

PHYSICAL AND TECHNICAL FEATURES

Quick Dry Filler: filler in powder form, made of gypsum plaster, selected quarry materials and cellulosic binder.

- Characterization (NFT 36-005): Family III class 3.
- Codification (EN 16-566): $G_3S_2V_0W_0A_0C_0R_0$.
- Mixing rate: add 400ml water per 1kg powder (40%).
- Application thickness: no depth limit.
- Capacity: 1,1kg fills 1L when mixed.
- Working time: 45 minutes.
- Setting time: 1h30.
- Overcoating: can be painted in 3 hours average time (after complete drying).
- Colour: white.
- Adhesion: filler/substrate (EN 16-566): > 0.8 Mpa.

USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or blade.
- Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
- Preservation: guaranteed for 12 months from purchase when used as intended, kept in its original sealed packaging and stored away from humidity. If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

PACKAGING

Box: 1kg.

RECOMMENDATIONS AND CARE FOR USE

- Do not apply under a temperature below 5°C and above 35°C nor under a hygrometry rate over 80%.
- Do not apply on overheated surfaces.
- Do not apply on polystyrene, on damp substrates, nor on wall paper, nor on exterior substrates.

SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS TO BE REFERRED TO

- BS EN 16566:2014 (Paints and varnishes. Fillers for internal and/or external works).

HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Interior Filler.

Always wear a dust mask when sanding.

Dispose of unused product and packaging responsibly at your local waste collection centre.

Safety data sheet available at www.toupret.co.uk

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products.

The product should be used as per the trade practices rules book and in reference to our recommendations.

The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates.

The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).

Manufacturer :

TOUPRET SA
24 rue du 14 juillet
91813 CORBEIL ESSONNES CEDEX France
RCS Evry B 964 201 859 – Mise à jour Avril 2025

TOUPRET
FILLERS FOR PROFESSIONALS