

# QUICK FILL LIGHTWEIGHT & READY MIXED

## ONE COAT REPAIRS ON WALLS & CEILINGS

- ♦ **WILL NOT SHRINK OR SLUMP**
- ♦ **EASY TO SAND**
- ♦ **NO NEED TO SPOT PRIME**
- ♦ **WILL NOT FLASH OR GRIN**



### PURPOSE

Interior Lightweight and ready to use, doesn't shrink and ready to paint in 30 minutes.

Ideal quick interior filler for one-coat repairs, gaps, cracks on walls and ceilings.

### SUBSTRATES

Quick Fill can be applied to any substrate either unpainted or painted:

- Gypsum plaster, plasterboards/drywall lining
- Old painted surfaces, cement, concrete, cellular concrete
- Breeze blocks, bricks, stone and primed wood.

### OVERCOATING

Quick Fill can be overcoated with any type of filler, paint or wall coating.

### PHYSICAL AND TECHNICAL FEATURES

Quick Fill: interior filler in ready mixed form made of lightweight material extracts and acrylic polymer.

- Characterization (NFT 36-005): Family III - class 2.
- Codification (EN 16-566) :  $G_3S_1V_0W_0A_0C_0R_0$ .
- Mixing rate: ready to use.
- Application thickness: no depth limit.
- Capacity: 1L fills 1L.
- Overcoating: can be painted in 30 Mins (for 1mm thickness) to 2 hours average time (after complete drying).
- Colour: white.
- Adhesion: filler/substrate (EN 16-566): > 0.5 Mpa.

### USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or blade.
- Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
- Preservation: guaranteed for 12 months from purchase when used as intended, kept in its original sealed packaging and stored away from sunlight and frost. If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

### PACKAGING

Tubs: 1L and 4L.

### RECOMMENDATIONS AND CARE FOR USE

- Do not apply under a temperature below 8°C and above 35°C nor under a hygrometry rate over 70%.
- Do not apply on overheated surfaces.
- Do not apply on polystyrene, on damp substrates, nor on wall paper, nor on exterior substrates.

### SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

### NORMATIVE DOCUMENTS TO BE REFERRED TO

- BS EN 16566:2014 (Paints and varnishes. Fillers for internal and/or external works).

### HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Quick Fill.

Always wear a dust mask when sanding.

Dispose of unused product and packaging responsibly at your local waste collection centre.

Contains biocidal products (Preservatives for products during storage): Contains 1,2-benzisothiazolin-3-one; C(M)IT/MIT (3:1). May produce an allergic reaction. Safety data sheet available at [www.toupret.co.uk](http://www.toupret.co.uk)

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



\* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).

#### Manufacturer :

TOUPRET SA  
24 rue du 14 juillet  
91813 CORBEIL ESSONNES CEDEX France  
RCS Evry B 964 201 859 – Mise à jour Avril 2025

**TOUPRET**  
FILLERS FOR PROFESSIONALS