

# STOP' CRACKS

## ACRYLIC PUTTY

- ◆ PREVENTS THE REAPPEARANCE OF CRACKS
- ◆ JOINTS BETWEEN WOOD AND MASONRY
- ◆ NO SANDING

### PURPOSE

Interior filler for repairs, gaps, cracks on walls and ceilings.

### SUBSTRATES

Stop' Cracks can be applied to either new or renovated substrates, unpainted or painted:

- Gypsum plaster, plasterboards/drywall lining
- Old painted surfaces, cement, concrete, cellular concrete, breeze blocks, bricks, stone.
- Between wood and masonry : door, plinth and window.

### OVERCOATING

Stop' Cracks can be overcoated with any type of filler, paint or wall coating.

### PHYSICAL AND TECHNICAL FEATURES

Stop' Cracks: filler made with acrylic.

- Characterization (NFT 36-005): Family III class 2.
- Codification (EN 16-566):  $G_3S_2V_0W_0A_0C_0R_0$ .
- Mixing rate: ready to use.
- Application thickness: 5 mm.
- Capacity: approx. 150 to 200 gr of product per linear meter of cracks.
- Working time: unlimited.
- Overcoating: can be painted in 24 hours average time (after complete drying).
- Colour: white.
- Adhesion: filler/substrate (EN 16-566): > 0.8 Mpa.

### USE AND STORAGE CONDITIONS

- Application tools: cartridge gun and filling knife.
  - Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
  - Preservation: guaranteed for 12 months from purchase when used as intended, kept in its original sealed packaging and stored away from humidity.
- If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.



### PACKAGING

- Cartridge: 300ml.

### RECOMMENDATIONS AND CARE FOR USE

- Do not apply under a temperature below 8°C and above 35°C nor under a hygrometry rate over 70%.
- Do not cover directly with polyurethane and epoxy paint in solvent phase.
- Do not apply on bonded coatings.

### SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

### NORMATIVE DOCUMENTS TO BE REFERRED TO

- BS EN 16566:2014 (Paints and varnishes. Fillers for internal and/or external works).

### HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Interior Filler. Dispose of unused product and packaging responsibly at your local waste collection centre.

Safety data sheet available at [www.toupret.co.uk](http://www.toupret.co.uk)

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products.

The product should be used as per the trade practices rules book and in reference to our recommendations.

The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorptivity substrates.

The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



\* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).

#### Manufacturer :

TOUPRET SA  
24 rue du 14 juillet  
91813 CORBEIL ESSONNES CEDEX France  
RCS Evry B 964 201 859 – Mise à jour Avril 2025

**TOUPRET**  
FILLERS FOR PROFESSIONALS