

## FINISHING FILLER

- ◆ SUPERIOR QUALITY FINISH
- ◆ VERY HIGH ADHERENCE
- ◆ REINFORCED HARDNESS
- ◆ REDUCES PAINT ABSORPTION
- ◆ EXTRA FINE AND WHITE
- ◆ EASY TO RUB DOWN



### PURPOSE

Ready to use smoothing surfacer for high quality extra fine finishing, interior use, manual application.

### SUBSTRATES

TX130 can be applied to :  
Cement, plasterboard, primed wood gypsum plaster, concrete and old painted surfaces.

### OVERCOATING

TX130 can be coated over by any type of matt or satin-finish, including epoxies and polyurethane, and wall covering.

### PHYSICAL AND TECHNICAL FEATURES

TX130 : filler in paste form for interior use, made of very fine calcium carbonates loads and resins.

- Characterization (NFT 36-005): Family III - Class 2.
- Codification (EN 16566):  $G_3S_1V_0W_0A_0C_0R_0$ .
- Mixing rate: ready to use.
- Application thickness: up to 1mm per coat.
- Coverage: Approx. 200-250 g/m<sup>2</sup> on flat substrate such as plasterboard.
- Setting time: second coat as soon as the filler is hard and dry to the touch.
- Overcoating: after completely dry.
- Colour: extra white.
- Adhesion: filler/substrate (EN 16566): > 0.5 Mpa.

### USE AND STORAGE CONDITIONS

- Application tools: with smoothing or surfacing blade.
- Tools cleaning: with water.
- Preservation: Toupret products are designed for high performance and are guaranteed for 12 months from purchase when used as intended.  
If the product is found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase. Product should be kept in its original sealed packaging and stored away from sunlight and frost.

### PACKAGING

- Bucket of 25 kg.

### RECOMMENDATIONS AND CARE FOR USE

- Do not apply under a temperature below 8°C and above 35°C nor under a hygrometry rate over 70%.
- Do not apply on overheated surfaces.
- Do not apply on damp substrates.
- Do not apply on polystyrene, nor on wall paper, nor on exterior substrates.

### SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

### NORMATIVE DOCUMENTS TO BE REFERRED TO

- NFT 16566: Coating Fillers for interior and/or exterior works.
- NFT 36-005: Characterization of paint products.
- DTU 59.1 (NFP 74-201): Building paint works.
- DTU 59.4 (NFP 74-204): wall papers and wall coverings processing.

### HEALTH AND SAFETY

It is recommended to wear a dust mask when sanding. It is recommended to wear protective gloves and eye protection during product application. Dispose of unused product and packaging responsibly at your local waste collection centre.

- No danger tag.
- Very low VOC emissions : < 0,01 %.
- Safety data sheets available on [touporet.com](http://touporet.com).

The data sheet information, especially the guidelines relevant to the application and final use of TX130 is provided in good faith and result from TOUPRET's experience and knowledge of the products.

The product should be used as per the trade practices rules book and in reference to our recommendations.

The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



\* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).