

FINE FINISH WOOD FILLER

EXTRA FINE SMOOTHING ON INTERIORS & EXTERIORS

- ◆ **COVERS SMALL DEFECTS**
- ◆ **FLEXIBLE**
- ◆ **QUICK DRYING**
- ◆ **COMPATIBLE WITH ALL PAINTS & COATINGS**



PURPOSE

Ready to use smoothing filler for extra fine finishes to all primed interior and exterior wood surfaces. Can be stained or painted with any type of conventional paint, varnish or stain after 1 hour.

SUBSTRATES

Fine Finish Wood Filler can be applied to primed wood surfaces. For optimal results, apply Wood Hardener beforehand.

OVERCOATING

Wood Filler can be overcoated by any type of filler, paint or coating.

PHYSICAL AND TECHNICAL FEATURES

- Fine Finish Wood Filler is a filler in ready mixed form, for interior or exterior use, made of mineral extracts and selected binders.
- Characterisation (NFT 36-005): Family IV - Class 4b.
- Codification (NFT 36-005): $G_3S_1V_0W_0A_0C_0R_0$.
- Mixing rate: ready to use.
- Application thickness: up to 1mm.
- Capacity: 450g per m².
- Setting time: second coat as soon as the filler is hard and dry to the touch.
- Overcoating: can be painted in 1 hour average time (after complete drying).
- Working time: unlimited.
- Colour: white.
- Adhesion: filler/substrate (NF T 30 608): > 0.8 Mpa.

USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or coating blade.
- Tool cleaning: after use, clean tools immediately with warm water.
- Preservation: Toupret products are designed for high performance and are guaranteed for 12 months from purchase when used as intended, kept in its original sealed packaging and stored away from sunlight and frost. If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

PACKAGING

Tube: 400g.

RECOMMENDATIONS AND CARE FOR USE

The times mentioned are indicative and depend on the substrate, the coat thickness, and the ambient conditions. Do not apply at a temperature below 5°C or above 35°C nor at a relative humidity over 80%.

SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS TO BE REFERRED TO

- NFT 30-608: Coating fillers for interior works and/or exterior.

HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Fine Finish Wood Filler. Always wear a dust mask when sanding. Dispose of unused product and packaging responsibly at your local waste collection centre.

Preservatives:

Contains 1,2-benzisothiazolin-3-one; C(M)IT / MIT (3:1). May produce an allergic reaction.

Safety data sheet available at www.toupret.co.uk

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).