



# SPECIAL FILLER FOR KITCHENS AND BATHROOMS - RENOVATE AND SMOOTH OLD TILES



## READY TO USE

- DAMP RESISTANT
- HIGH-BUILD, OPAQUE FINISH
- EASY TO APPLY AND SAND

## USAGE

For filling holes and cracks, up to 5 mm deep, and smoothing walls and ceilings in rooms subject to damp, such as kitchens and bathrooms. Ideal for renovating old wall tiles and ceramic coverings.

## SUBSTRATES

Apply to rough or painted surfaces. Gypsum plaster, plasterboard, gypsum blocks, glass cloth, coatings, concrete, mortar, render, cement, breeze blocks, textured finishes, wall tiles and all flexible substrates.

## MIXING RATE

Ready to use

## INDOOR / OUTDOOR

INDOOR

## WORKING TIME

illimited

## APPLICATION THICKNESS

5mm

## SUBSTRATE PREPARATION

The substrate must be hard, dry, sound, clean,solid substrates.

## HOW TO USE

- 1 - Fill grout lines : using a filling knife, apply the product generously across the joint and then smooth out along the joint. Allow to dry and then remove any excess thickness to reduce the need for sanding between layers.

Smooth the tiles : apply product in a series of areas of approximately 1 sq. m, using a 20cm taping knife. Hold the blade at an acute angle to apply sufficient coating to cover the tiles. A second layer may be necessary if the tiles are very unevenor have relief designs on them.

- 3 - Sand when the compound is dry and ready to paint.

## SECOND COAT TIME

8h

## READY TO PAINT

12-48h

## OVERCOATING

Damp-resistant paint

## NATURE

Paste

## COLOR

white

## STORAGE

AFTER USE: Carefully close the packaging. STORAGE: One year from date of purchase in closed original packaging, away from frost and sunlight.

## ADVICES

Must be recovered with a finish. Do not apply directly on wall paper

## HEALTH AND SAFETY

Think about health and safety. It is recommended that you wear a mask when sanding. It is recommended to wear gloves while applying the filler.

Contains 1,2-benzisothiazolin-3-one and reaction mass of : 5-chloro-2-methyl-4-isothiazolin-3-one [EC n° 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC n° 220-239-6] (3 :1). May produce an allergic reaction.

## USING CONDITIONS

Do not apply in temperatures below 8°C or above 35°C.

## PACKAGING

5 kg

## CLEANING

To clean your tools effectively, wait until the product is completely dry and then scrape your tools. Water is not needed.

## NOTE

Drying, coverage and painting times are given as an indication and depend on the thickness applied, the medium and the ambient conditions.

TOUPRET UK Ltd.  
Capital Business Center UNIT 58  
22 Carlton Road  
South Croydon CR2 OBS  
Tel : +44 (0) 208 916 2134 - Fax : +44 (0) 208 916 2136  
<https://www.toupret.co.uk>

TOUPRET SA - 24 rue du 14 Juillet - 91813 Corbeil-Essonnes Cedex France - RCS Evry B 964 201 859 octobre 2019