



## Magic'levelling kit - complete, easy renovation kit for levelling rough surfaces

Apply using the roller / Spread using the serrated blade / Smooth using the smoothing blade



- + easier +Faster
- 80% less sanding
- Highbuild finish up to 5mm

### USAGE

The MAGIC' LEVELLING KIT is ideal for renovating walls and ceilings that are very uneven or very damaged. Using its dedicated tools and its exclusive formula, you can level the most damaged surfaces, former renderings or fiberglass cloth, without any technical procedures.

### SUBSTRATES

Excellent adherence to indoor surfaces, walls, ceilings, bare or painted. Ideal for uneven surfaces such as rendering, fiberglass cloth, droplets or very damaged surfaces

### MIXING RATE

Ready to use

### INDOOR / OUTDOOR

INDOOR

### WORKING TIME

illimited

### APPLICATION THICKNESS

5mm

### SUBSTRATE PREPARATION

The substrate must be hard, dry, sound, clean,solid substrates.

### HOW TO USE

- 1 - Remove any dust
- 2 - Apply a generous amount of filler using the roller to cover up all defects
- 3 - Spread the filler using the serrated blade.
- 4 - As soon as the first layer is dry, apply one fine layer of filler using the roller.
- 5 - Smooth the filler using the smoothing blade, removing excess material.
- 6 - For the best results, sand once the filler is dry.

### SECOND COAT TIME

6-8h

### READY TO PAINT

12-24h

## OVERCOATING

Must be covered by any type of paint, decorative filler, wallpaper or other covering.

## NATURE

Paste

## COLOR

White

## STORAGE

Product guaranteed for 12 months from the date of purchase, in its original packaging, kept closed and away from extreme temperatures.

## ADVICES

Tip: you can repeat steps 3 and 4 as many times as needed (leave 6 to 8 hours between each subsequent layer). Do not apply directly on wallpaper. For a satin paint finish, apply a layer of The MAGIC' FINISHING KIT using the roller and the smoothing blade.

## HEALTH AND SAFETY

Gloves are recommended for application. To protect your health, a mask should be worn when sanding.

Contains 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

## USING CONDITIONS

Do not apply in temperatures below 8°C or above 35°C.

## PACKAGING

20 kg

## CLEANING

To clean your tools effectively, wait until the product is completely dry and then scrape your tools. Water is not needed.

## NOTE

Drying, coverage and painting times are given as an indication and depend on the thickness applied, the medium and the ambient conditions.

TOUPRET UK Ltd.  
Capital Business Center UNIT 58  
22 Carlton Road  
South Croydon CR2 OBS  
Tel : +44 (0) 208 916 2134 - Fax : +44 (0) 208 916 2136  
<https://www.toupret.co.uk>

TOUPRET SA - 24 rue du 14 Juillet - 91813 Corbeil-Essonnes Cedex France - RCS Evry B 964 201 859 octobre 2019