

MAGIC'TILE COVERING KIT - COMPLETE, EASY COATING KIT FOR SMOOTHING OVER TILES



Fill the joints using the spatula. Apply filler using the roller. Smooth filler using the blade

- Wall Tiles
- Excellent adherence
- Smooth, paintable finish
- 4 sq.m approx.

USAGE

SUBSTRATES

All indoor materials, including wall tiling, porcelain, mosaic, etc

MIXING RATE

Ready to use

INDOOR / OUTDOOR

INDOOR

WORKING TIME

illimited

APPLICATION THICKNESS

5mm

SUBSTRATE PREPARATION

The substrate must be hard, dry, sound, clean, solid substrates.

HOW TO USE

- 1 - Fill the tile joints using the red spatula. Allow to dry for 12/24 hrs. Sand.
- 2 - Apply filler using a roller to cover your tiles.
- 3 - Smooth it using the purple blade with a closed angle of around 45° so as to leave the thickness needed to cover the tiling***. Leave to dry for 24 to 48 hours before painting.

***If the contours of the tiling joints are still visible or if a natural micro-blistering phenomenon appears, apply a second very fine layer of filler. Hold the purple blade with a nopen angle of 90° and exert pressure to remove the excess filler. Leave to dry for 12 to 24 hours and sand before painting

SECOND COAT TIME

12-24h

READY TO PAINT

24-48h

OVERCOATING

Should be coated with paint, a decorative filler or any other coating that is resistant to damp rooms.

NATURE

Paste

COLOR

White

STORAGE

Product guaranteed for 12 months from the date of purchase, in its original packaging, kept closed and away from extreme temperatures.

ADVICES

Do not apply directly on wallpaper. On satin or glossy paint, sand lightly or wash before application. Do not apply direct and continuous water projections, such as shower spray, onto surfaces. Do not apply on work surfaces or on floors.

HEALTH AND SAFETY

Gloves are recommended for application. To protect your health, a mask should be worn when sanding.

Contains 1,2-benzisothiazolin-3-one and reaction mass of:
5-chloro-2-methyl-4-isothiazolin-3-one [EC n° 247-500-7]
and 2-methyl-4-isothiazolin-3-one [EC n° 220-239-6] (3 :1).

USING CONDITIONS

Do not apply in temperatures below 8°C or above 35°C.

PACKAGING

5 kg

CLEANING

To clean your tools effectively, wait until the product is completely dry and then scrape your tools. Water is not needed.

NOTE

Drying, coverage and painting times are given as an indication and depend on the thickness applied, the medium and the ambient conditions.

TOUPRET UK Ltd.
Capital Business Center UNIT 58
22 Carlton Road
South Croydon CR2 OBS
Tel : +44 (0) 208 916 2134 - Fax : +44 (0) 208 916 2136
<https://www.toupret.co.uk>

TOUPRET SA - 24 rue du 14 Juillet - 91813 Corbeil-Essonnes Cedex France - RCS Evry B 964 201 859 octobre 2019