

RENOVATING FILLER FOR ROUGH SURFACES ESPECIALLY FOR RENDER, GLASS CLOTH AND DAMAGED WALLS



READY TO USE

- IDEAL FOR DAMAGED, TEXTURED WALLS
- HIGH-BUILD FINISH
- EASY TO APPLY

USAGE

For renovating and smoothing damaged walls or with contours up to 5mm deep.

SUBSTRATES

Applied to rough or painted walls, render, glass cloth, old decorative coatings, textured finishes, gypsum plaster, plasterboard, gypsum blocks, concrete, cement, brick, stone

MIXING RATE

Ready to use

INDOOR / OUTDOOR

INDOOR

WORKING TIME

illimited

APPLICATION THICKNESS

5mm

SUBSTRATE PREPARATION

The substrate must be hard, dry, sound, clean, solid substrates.

HOW TO USE

- 1 - Remove any dust
- 2 - Apply the coating in a series of areas of approximately 1 sq. m. Using a smoothing tool or 20cm taping knife, spread the coating roughly in a thick layer and then even out the surface by spreading the coating uniformly.
- 3 - When the coating starts to dry, remove the most obvious irregularities (lumps, excess thicknesses) with the edge of the blade, so as to reduce the need for sanding. If a second layer is necessary, wait until the first one is completely dry.
- 4 - Sand when the compound is dry and ready to paint.

SECOND COAT TIME

12-24h

READY TO PAINT

24-48h

OVERCOATING

Paint • Decorative coating • Wallpaper

NATURE

Paste

COLOR

White

STORAGE

AFTER USE: Carefully close the packaging. STORAGE : one year from date of purchase in closed original packaging, away from frost and sunlight.

ADVICES

Must be recovered with a finish. Do not apply directly on wall paper.

HEALTH AND SAFETY

Think about health and safety. It is recommended that you wear a mask when sanding. It is recommended to wear gloves while applying the filler.

Contains 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

USING CONDITIONS

Do not apply in temperatures below 8°C or above 35°C.

PACKAGING

10 - 20 kg

CLEANING

To clean your tools effectively, wait until the product is completely dry and then scrape your tools. Water is not needed.

NOTE

Drying, coverage and painting times are given as an indication and depend on the thickness applied, the medium and the ambient conditions.

TOUPRET UK Ltd.
Capital Business Center UNIT 58
22 Carlton Road
South Croydon CR2 OBS
Tel : +44 (0) 208 916 2134 - Fax : +44 (0) 208 916 2136
<https://www.toupret.co.uk>

TOUPRET SA - 24 rue du 14 Juillet - 91813 Corbeil-Essonnes Cedex France - RCS Evry B 964 201 859 octobre 2019